

Style: 8812

Material: Nylon liner with nitrile foam/ water based PU – palm dipped

Application: recommended for all kinds of food

The article meets relevant requirements in:

European Regulation (EC) No. 1935/2004

European Regulation (EC) No. 2023/2006 (GMP)

European Regulation (EU) No. 10/2011.

The Regulation (EU) No. 10/2011 excludes rubber materials, instead reference to Bfr

(Bundesinstitut für Risikobewertung).

The overall migration test performed according to EN 1186 and resulted as follows:

Simulant	Permissible	Test Conditions	Result of overall
	limit (mg/dm ²)	time and temperature	migration, mg/dm ²
Acetic acid, 3 %	10	$2.0 \text{ hr(s)}, 70^{\circ}\text{C}$	6.8
Ethanol, 10 %	10	2,0 hr(s), 70°C	< 3.0
Ethanol, 95%	10	2,0 hr(s), 60°C	6.7
Isooctane	10	0,5 hr(s), 40°C	4.1

Ratio of food contact surface area to volume used to establish the compliance of the article; $6 \text{ dm}^2/\text{kg}$

Test institute: SGS-CSTC, 198 Kezhu Road, Scientech Park, Guangzhou, China

Reference:

CANHG1807690501 CANHG1718473901

2018-05-18

Lena Prytz

Senior Operation Manager